

Photo		
LCD Display	Display Type	12" TFT-LCD
	Resolution	1024*768
	Brightness	400 cd/m²
	Viewing Angle	-89~89° (H), -89~89° (V) C9(CR≥10)
	Backlight	LED
	Backlight Life MTBF (hrs))	30000 Hours
	Max color	16.7M
	Contrast Ratio	1000:1
Touch Screen	Touch Panel	Five wire Resistive touch(Capacitive touch optional)
	Connection Port	USB 2.0
	Light transmittance	> 85%
	Click Life time	250 g Pressure, 10 Million times
Mechanical	Color	Grey
	Display Connection	VGA, HDMI
	Size	318.8 x 245 x 45.5 mm
	Opening Hole size	NA
	Mounting	Embedded Mounting/ Vesa Mounting
	Weight (kg)	NA
Environment	Operational Temperature	-20 ~ 70° C
	Storage Temperature	-30 ~ 80° C
	Relative Humidity	95% @ 40° C (non-condensing)
	IP rate	Front panel IP65
	Anti-Vibration	1.5Grms@5~500Hz, random, 1 hr/axis
	Anti-Shock	10g acceleration, 11ms duration
Accessories	USB Cable 1.5 meters	
	HDMI cable 1.5 meters	
	Mounting brackets(embedded mounting)	
	Vesa mounting optional	

12.1 inch Monitor Drawing

■ mm

