

cMT X Series Model Types

Standard

Enhanced for smart applications

The cMT X Standard features video streaming and mobile monitoring, along with advanced EasyBuilder Pro objects to meet diverse application needs.

Advanced

All-around smart HMI

The cMT X Advanced offers the most comprehensive HMI and EasyBuilder Pro features. It supports various IIoT protocols, and excels in cross-platform data integration.

Handheld HMI

Freedom to operate on the move

Handheld HMI breaks free from fixed setups, allowing movement within cable range for on-site parameter adjustment—ideal for multi-station monitoring.

Headless HMI

Going beyond size boundaries

Headless HMI works independently without a screen and can be monitored on apps or on external screens of various sizes.



Naming Convention

cMT 3 07 2 X * ()

Series Name

cMT X

Category

2 Standard
3 Advanced

Screen Size

05 4.3 " 12 12.1 "
07 7 " 15 15 "
09 9.7 " 16 15.6 "
10 10.1 " 21 21.5 "

Ethernet Port

2 Dual Ethernet Ports
6 Single Ethernet Port
8 Dual Ethernet Ports

1~9 Appearance Difference

H High Resolution
P Projected Capacitive Touch (PCAP)
T Wide Temperature
M Mobile Handheld HMI

(R) Built-in RFID

(L) High Brightness

(W) HTML5 Web Panel

(iV) Built-in cMT Viewer

Note: (V#) suffix marks CPU differences.